PAGE 4112" RCVD AT 4115/2004 7:41:13 PM [Eastern Daylight Time] " SVR:USPTO-EFXRF-110" DNIS:8729306 " CSID:9728945619" DURATION (mm-55):03-12 Attorney Docket No. NC17054

## Claims

Claims 1- 13 (Canceled)

1. (Original) A method for configuring a electronic device mobile station for operation, said method comprising the steps of:

> storing a plurality of sets of configuration data in a memory device in said electronic device mobile station, wherein each set of configuration data defines an operating configuration for system/network independent features on said electronic devicemobile station;

> receiving identity data at said electronic device mobile station; determining, in response to receiving said identity data, a selected set of configuration data of said plurality of sets of configuration data; and

configuring said electronic devicemobile station for operation according to said selected set of configuration data.

- 2. (Original) The method of claim 1, wherein said step of receiving identity data comprises receiving identity data from a subscriber identity module inserted in said electronic devicemobile station.
- 3. (Currently Amended) The method of claim 2, wherein said subscriber identity module comprises a GSM-Global System for Mobile Communication subscriber identity module.
- 4. (Currently Amended) The method of claim 3, wherein said step of determining a selected set of said plurality of sets of configuration data comprises the steps of:

determining an mobile network code/mobile country code MCC/MNC from said identity data; and

PACE 5112 \* RCVD AT 4112/2004 F1:14 PM [Eastern Daylight Time] \* SVR: USPTO-EFXRF-110 \* DNIS:8729306 \* CSID:9728945619 \* DURATION (mm-ss):03-12 Attorney Docket No. NC17054

> matching said mobile network code/mobile country codeMCC/MNC to a selected set of said plurality of sets of configuration data.

5. (Currently Amended) The method of claim 3, wherein said step of determining a selected set of said plurality of configuration data comprises the steps of:

> determining a GID-group identifier from said identity data; and matching said GID group identifier to a selected set of said plurality of sets of configuration data.

- 6. (Original) The method of claim 1, wherein said step of receiving identity data comprises receiving identity data programmed into said electronic device mobile station upon initialization for use.
- 7. (Currently Amended) The method of claim 6, wherein said identity data comprises a SID/SOC system identification/system operator.
- 8. (Currently Amended) An apparatus for configuring a electronic device mobile station for operation, said apparatus comprising:

a memory device for storing a plurality of sets of configuration data in said electronic devicemobile station, each of said plurality of sets of configuration data defining an operating configuration for system/network independent features on said electronic devicemobile station;

an input device for receiving identity data at said electronic devicemobile station; and

a processor coupled to said memory device and said input device, said processor for receiving said identity data from said input device, determining a selected set of said plurality of sets of configuration data based on said identity data, and configuring said

MOKIU IPR

**DAGE** 6112.\* RCVD AT 411512004 7:41:13 PM [Eastern Daylight Time]. SVR:USPTO-EFXRF-110.\* DNIS:8729306.\* CSID:9728945619.\* DURATION (mm-ss):03-12

electronic device mobile station for operation according to said selected set of configuration data.

- (Original) The apparatus of claim 8, wherein said identity data includes identity data programmed into said electronics device upon initialization for use.
- 10. (Currently Amended) The apparatus of claim 9, wherein said identity data comprises an SID/SOG system identification/system operator.
- 11. (Original) The apparatus of claim 8, wherein said apparatus further comprises a socket coupled to said input device, said socket for receiving a subscriber identity module, and wherein said identity data received by said input device comprises subscriber identity module data.
- 12. (Currently Amended) The apparatus of claim 11, wherein said identity data includes an mobile network code/mobile country code/MCC/MNC, and wherein said processor determines said selected set of said plurality of sets of configuration data by matching said mobile network code/mobile country code/MCC/MNC to a selected set of said plurality of sets of configuration data.
- 13. (Currently Amended) The apparatus of claim 11, wherein said identity data includes an GID group identifier, and wherein said processor determines said selected set of said plurality of sets of configuration data by matching said GID group identifier to a selected set of said plurality of sets of configuration data.
- 14. (New) A method for configuring a mobile station for operation, said method comprising the steps of:

storing a plurality of sets of configuration data in a memory device in said mobile station, wherein each set of configuration data defines an operating configuration for wake-up graphics on said mobile station;

receiving identity data at said mobile station;

ST-CC:(21:13 PM [Eastern Daylight Time] \* SVR: USPTO-EFXRF-110 \* DNIS-18729306 \* CSID:9278545619 \* DURATION (mm-ss)-1971 Attorney Docket No. NC17054

> determining, in response to receiving said identity data, a s lected set of configuration data of said plurality of sets of configuration data; and

configuring said mobile station for operation according to said selected set of configuration data.

(New) A method for configuring a mobile station for operation, said 15. method comprising the steps of:

> storing a plurality of sets of configuration data in a memory device in said mobile station, wherein each set of configuration data defines an operating configuration for hiding or displaying menu items on said mobile station;

receiving identity data at said mobile station;

determining, in response to receiving said identity data, a selected set of configuration data of said plurality of sets of configuration data; and

configuring said mobile station for operation according to said selected set of configuration data.

16. (New) A method for configuring a mobile station for operation, said method comprising the steps of:

> storing a plurality of sets of configuration data in a memory device in said mobile station, wherein each set of configuration data defines an operating configuration for subscriber identity module lock settings on said mobile station:

receiving identity data at said mobile station;

determining, in response to receiving said identity data, a selected set of configuration data of said plurality of sets of configuration data: and

DAGE 8/12" RCVD AT 4/15/2004 7:13 PM [Eastern Daylight Time] SVR: USPTO-EFXRF-1/0" DNIS:8729306 "CSID:9728045619" DURATION (mm-ss):03-12

configuring said mobile station for operation according to said selected set of configuration data.

17. (New) A method for configuring a mobile station for operation, said method comprising the steps of:

storing a plurality of sets of configuration data in a memory device in said mobile station, wherein each set of configuration data defines an operating configuration for encryption and decryption features on said mobile station;

receiving identity data at said mobile station;

determining, in response to receiving said identity data, a selected set of configuration data of said plurality of sets of configuration data; and

configuring said mobile station for operation according to said selected set of configuration data.

18. (New) An apparatus for configuring a mobile station for operation, said apparatus comprising:

a memory device for storing a plurality of sets of configuration data in said mobile station, each of said plurality of sets of configuration data defining an operating configuration for wake-up graphics on said mobile station;

an input device for receiving identity data at said mobile station; and

a processor coupled to said memory device and said input device, said processor for receiving said identity data from said input device, determining a selected set of said plurality of sets of configuration data based on said identity data, and configuring said

PAGE 9112 \* RCVD AT 4112004 F1:13 PM (Eastern Daylight Time) \* SY:05PTO-EFXRF-110 \* DNIS:8729306 \* CSID:9728945619 \* DURATION (mm-ss):03-12 Attorney Docket No. NC17054

> mobile station for operation according to said selected set of configuration data.

(New) An apparatus for configuring a mobile station for operation, said 19. apparatus comprising:

> a memory device for storing a plurality of sets of configuration data in said mobile station, each of said plurality of sets of configuration data defining an operating configuration for hiding or displaying menu items on said mobile station;

an input device for receiving identity data at said mobile station; and

 a processor coupled to said memory device and said input device, said processor for receiving said identity data from said input device, determining a selected set of said plurality of sets of configuration data based on said identity data, and configuring said mobile station for operation according to said selected set of configuration data.

(New) An apparatus for configuring a mobile station for operation, said 20. apparatus comprising:

> a memory device for storing a plurality of sets of configuration data in said mobile station, each of said plurality of sets of configuration data defining an operating configuration for subscriber identity module lock setting features on said mobile station;

an input device for receiving identity data at said mobile station; and

a processor coupled to said memory device and said input device, said processor for receiving said identity data from said input device, determining a selected set of said plurality of sets of

PAGE 10/17 \* RCVD AT 4/15/2004 7:41:13 PM [Eastern Daylight Time] \* SVR:USPTO-EFXRF-1/0 \* DNIS:8729306 \* CSID:9728945619 \* DURATION (mm-ss):03-12

configuration data based on said identity data, and configuring said mobile station for operation according to said selected set of configuration data.

21. (New) An apparatus for configuring a mobile station for operation, said apparatus comprising:

a memory device for storing a plurality of sets of configuration data in said mobile station, each of said plurality of sets of configuration data defining an operating configuration for encryption and decryption features on said mobile station;

an input device for receiving identity data at said mobile station; and

a processor coupled to said memory device and said input device, said processor for receiving said identity data from said input device, determining a selected set of said plurality of sets of configuration data based on said identity data, and configuring said mobile station for operation according to said selected set of configuration data.

E9X: 3528945619

P. 10